

Tiled finish to window cills (if window shown on plot specific drawings).

Egstow Park Phase 2
Core Range
Sales Specification & Finishes.
June 2024
R9076-SMH-24-XX-SP-K-5400 Rev C01
Plots 201-207, 214-219, 234-254, 346 & 347 only

H4B1192 - The Kea (D)

H4B1192 - The Chichester (D)

H4B1362 - The Barlow (D)

H4B1371 - The Paris (D)

H4B1371D - The Baris (D/S)

H4B1454 - The Garnet (D)

D - Detached. S - Semi Detached. A choice of Moores / Symphony base and wall units fitted with soft closers to drawers and doors. gocm tall wall units including boiler housing except when boiler is in utility (Refer to working drawings). A choice of 40mm laminated worktops and matching upstands with stainless steel splashback behind hob. Stainless steel built in tall double fan oven with gocm six burner gas hob and gocm chimney extractor hood. Refer to the kitchen design. stainless steel built under single fan oven with 6ocm four burner gas hob and 6ocm chimney extractor hood. Refer to the kitchen design. Integrated fridge/freezer 50/50 split. Space for fridge/freezer. American Fridge Freezer (Almond Only) - Plumbed in. Plumbing for washing machine or washer dryer space. (Washing machine or washer dryer available as a sales extra). Plumbed freestanding washer dryer. Integrated dishwasher. Removable kitchen unit & pre-plumbing for integrated dishwasher. (Dishwasher available as a sales extra). Franke Antea stainless steel single inset sink bowl and drainer with Franke Athena chrome mixer tap. (Delux offer changes to a bowl and a half sink). Downlights to kitchen area and low voltage under wall unit lighting. 4 way spotlight fitting to kitchen area. Utility / Utility Cupboard / Laundry (where applicable) Units to match main kitchen. A choice of 40mm laminated worktops and matching upstands. Plumbing for washing machine or washer dryer space. (Washing machine or washer dryer available as a sales extra). Tumble dryer space. (Space only - appliance to be self purchased & installed) Franke Antea stainless steel single inset sink bowl and drainer with Franke Athena chrome mixer tap. (Refer to working drawing for placement). 2 burner electric hob. Bathroom Ideal Standard i. Life acrylic water saving bath with Roper Roads bath panel and frameless hinged Merlyn shower screen and thermostatic shower with connection hose from bath mixer taps to Ideal Rain S3 shower head. Full height tiling to perimeter of bath. ldeal Standard i. Life acrylic water saving bath with Roper Roads bath panel without shower and screen with Cerabase Single Lever Bath Filler. Half height tiling to perimeter of bath JT Fusion Shower tray and Merlyn sliding shower screen with Ideal Standard thermostatic shower. Full height tiling to shower enclosure JT Fusion Shower tray and Merlyn hinged shower screen (and fixed side panel where applicable) with Ideal Standard thermostatic shower. Full height tiling to shower Ideal Standard i.Life A, close-coupled WC with RimLS+, slow-close seat & cover and 4/2.6 litre cistern. Ideal Standard iLife A 50cm 1 tap-hole washbasin with full height pedestal, with Ideal Standard Cerabase single-lever basin mixer and click waste – chrome. Half height wall tiling behind sanitaryware Tiled finish to window cills (if window shown on plot specific drawings). Downlights. Low Energy batten light fitting. Master En-suite (where provided) JT Fusion Shower tray and Merlyn hinged shower screen (and fixed side panel where applicable) with Ideal Standard thermostatic shower. Full height tiling to shower JT Fusion Shower tray and Merlyn bi-folding shower screen with Ideal Standard thermostatic shower. Full height tiling to shower enclosure. JT Fusion Shower tray and Merlyn sliding shower screen with Ideal Standard thermostatic shower. Full height tiling to shower enclosure. Ideal Standard i. Life acrylic water saving bath with Roper Roads bath panel and frameless hinged Merlyn shower screen and thermostatic shower with connection hose from bath mixer taps to Ideal Rain S3 shower head. Full height tiling to perimeter of bath. Ideal Standard i.Life A, close-coupled WC with RimLS+, slow-close seat & cover and 4/2.6 litre cistern. Ideal Standard iLife A 50cm 1 tap-hole washbasin with full height pedestal, with Ideal Standard Cerabase single-lever basin mixer and click waste – chrome. Half height wall tiling behind sanitaryware. Tiled finish to window cills (if window shown on plot specific drawings). Downlights. Low Energy batten light fitting. Second En-suite (where provided) JT Fusion Shower tray and Merlyn hinged shower screen (and fixed side panel where applicable) with Ideal Standard <u>electric</u> shower. Full height tiling to shower enclosure. JT Fusion Shower tray and Merlyn sliding shower screen with Ideal Standard <u>electric</u> shower. Full height tiling to shower enclosure. Ideal Standard i.Life acrylic water saving bath with Roper Roads bath panel and Merlyn shower screen and Ideal Standard electric shower with connection hose from bath mixer taps to Ideal Rain S3 shower head. Full height tiling to perimeter of bath. Ideal Standard i.Life A, close-coupled WC with RimLS+, slow-close seat & cover and 4/2.6 litre cistern. Ideal Standard iLife A 50cm 1 tap-hole washbasin with full height pedestal, with Ideal Standard Cerabase single-lever basin mixer and click waste – chrome. Half height wall tiling behind sanitaryware.

ST. MODWEN HOMES Downlights.	Egstow Park Phase 2 Core Range Sales Specification & Finishes. June 2024 R9076-SMH-24-XX-SP-K-5400 Rev C01 Plots 201-207, 214-219, 234-254, 346 & 347 only	H3B922D - The Kea (D)	H4B1192 - The Chichester (D)	H4B1362 - The Barlow (D)	H4B1371 - The Paris (D)	H4B1371D - The Paris (D/S)	H4B1454 - The Garnet (D)
Low Energy batten light fitting.							
Cloakroom / WC							
JT Fusion shower tray with Merlyn semi frameless bi-fold shower scre shower perimeter	en and Ideal Standard <u>electric</u> shower mixer with Ideal Rain S3 shower head. Full height tiling to						
deal Standard i.Life S, Compact close-coupled WC with slow-close seat & cover and 4/2.6 litre cistern.				•	•	•	•
deal Standard i.Life A 40cm handrinse basin with 1 tap-hole and full height pedestal with Ideal Standard Cerabase single-lever basin mixer and click waste — chrome				•	-	•	-
Wall tiling splashback above basin. Bedrooms		•	•	•		•	•
Wardrobe to Bed 1, fitted with sliding, mirrored doors and threshold:	strips.						
Open walk in wardrobe with clothes rails and shelving							
Wardrobe to Bed 1, door fitted with lever handles and latch to match Electrical	the main doors. Clothes rails and shelving to be provided.			-			•
Electrical sockets in white to NHBC / LABC requirements.		•	•	-	•	•	•
Lounge media plate pre-wired for BT & Terrestrial Digital TV and prov Master bedroom pre-wired for Terrestrial Digital TV and provision for			•	•	•		
Lounge and master bedroom provided with 1no. Deta double socket							
Family Room pre-wired for Terrestrial Digital TV.				•			•
Data (telephone) point in bedroom 1 (Refer to Working drawings for e Data (telephone) point in bedroom 2 (Refer to Working drawings for e	·	-			•		
Data (telephone) point in study (Refer to Working drawings for exact	·				-	-	
2no. Deta double sockets and a data (telephone) point to allow for ho	me working (Refer to Working drawings for exact location).	-	•	•	•	•	•
Door bell Low energy lighting to Building Regulations standard.			•				
	or directly adjacent to the dwelling). All homes with detached garages within curtilage to include	_	_	_	_		
ducting for future fit of lighting and sockets. Refer to plot specific dra	, , , , , , , , , , , , , , , , , , , ,	•				•	•
Heating Gas fired central heating with white radiators and thermostatic valve.	s (as specified on heating designs)				_		_
Thermostat with digital display. (Refer to Working drawings for exact		-	_	_	_	_	
Thermostat with digital display. (Refer to Working drawings for exact	: location). Double zone		•	•	•		•
Internal & External Windows & Doors	have specified) frames to be white with scaled double glazed units, shrome iranmongers and						
window restrictors (where applicable).	here specified) frames to be white with sealed double glazed units, chrome ironmongery and	•	•	•	•	•	•
UPVC Utility doors to side/rear, frames and doors to be white.				٠			٠
Insulated GRP (Glass Reinforced Plastic) Pas :24 front door (where applicable) - style to be HNG1H, frames to be white, doors to be grey (RAL7016) to outside and white inside.				•	•	-	•
Garador Horizon up & over steel garage door with Plastisol finish (wh	ere applicable), to be grey (RAL7106).	-					
Suffolk grained, vertical grooved white water based gloss internal doors.				•	•	-	•
Insulated, drop down, loft hatch.				•			•
Insulated, drop down, steel, fire rated loft hatch (to 2.5/3 storey homes). Fire doors internal. Satin stainless steel finished curved mitred lever door furniture throughout.					•	•	
Decoration							
All walls to be finished in white matt emulsion. Ceiling finished in white matt emulsion.					•		
White oil based gloss painted staircase with white gloss balustrades,	handrails and newel caps.						
White oil based gloss painted staircase and balustrades with hardwoo		•	•	•	•	•	•
White oil based gloss painted 144mm x 18mm square edge MDF skirti White oil based gloss painted 69mm x 22mm square edge MDF archit							
		•	•		•	•	•
White oil based gloss painted woodwork.		_	_	_	_		
Security			,			-	
		-			-		
Security Multi-point door locking to external / french / patio / bi-fold doors		•	•		•	•	_
Security Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements.					•	÷	•
Security Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements.		_	_	_	_		
Security Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements. Through door viewer and chain PIR controlled external light to front door. Pre-wire for external lights to rear and side doors.		_	:	:	•	•	
Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements. Through door viewer and chain PIR controlled external light to front door. Pre-wire for external lights to rear and side doors. External Features		:				÷	
Security Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements. Through door viewer and chain PIR controlled external light to front door. Pre-wire for external lights to rear and side doors.		•				:	
Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements. Through door viewer and chain PIR controlled external light to front door. Pre-wire for external lights to rear and side doors. External Features Front garden graded, turfed and planted as applicable.	; (type and position as indicated on site layouts).						
Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements. Through door viewer and chain PIR controlled external light to front door. Pre-wire for external lights to rear and side doors. External Features Front garden graded, turfed and planted as applicable. Rear garden graded and turfed as applicable. Fencing - 1800mm timber fencing with gate to rear or side boundaries. Paths - Buff paving flags as indicated on site layouts.						•	
Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements. Through door viewer and chain PIR controlled external light to front door. Pre-wire for external lights to rear and side doors. External Features Front garden graded, turfed and planted as applicable. Rear garden graded and turfed as applicable. Fencing - 1800mm timber fencing with gate to rear or side boundaries	ges and rear)						
Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements. Through door viewer and chain PIR controlled external light to front door. Pre-wire for external lights to rear and side doors. External Features Front garden graded, turfed and planted as applicable. Rear garden graded and turfed as applicable. Fencing - 1800mm timber fencing with gate to rear or side boundaries. Paths - Buff paving flags as indicated on site layouts. (900mm wide path to front entrance, 600mm wide path to side passa	ges and rear)						
Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements. Through door viewer and chain PIR controlled external light to front door. Pre-wire for external lights to rear and side doors. External Features Front garden graded, turfed and planted as applicable. Rear garden graded and turfed as applicable. Fencing - 1800mm timber fencing with gate to rear or side boundaries. Paths - Buff paving flags as indicated on site layouts. (goomm wide path to front entrance, 600mm wide path to side passa Patio - Buff paving flags outside patio door as indicated on site layout Terrace Balconies - Buff paving flags to external walk-out balconies Slim profile, grey GRP canopy above entrance door	ges and rear) t.						
Multi-point door locking to external / french / patio / bi-fold doors Windows fitted with window locks with key, unless fire escape. Mains supply smoke detectors to Building Regulation requirements. Carbon monoxide alarm to Building Regulation requirements. Through door viewer and chain PIR controlled external light to front door. Pre-wire for external lights to rear and side doors. External Features Front garden graded, turfed and planted as applicable. Rear garden graded and turfed as applicable. Fencing - 1800mm timber fencing with gate to rear or side boundaries. Paths - Buff paving flags as indicated on site layouts. (goomm wide path to front entrance, 600mm wide path to side passa Patio - Buff paving flags outside patio door as indicated on site layout Terrace Balconies - Buff paving flags to external walk-out balconies	ges and rear) t.						

Approved for Construction



Egstow Park Phase 2
Core Range
Sales Specification & Finishes.
June 2024
R9076-SMH-24-XX-SP-K-5400 Rev C01
Plots 201-207, 214-219, 234-254, 346 & 347 only

H3B922D - The Keα (D)	H4B1192 - The Chichester (D)	H4B1362 - The Barlow (D)	H4B1371 - The Paris (D)	■ H4B1371D - The Paris (D/S)	■ H4B1454 - The Garnet (D)
	((

Black gutters and downpipes.